

OutdoorPower

Safe and robust IP rated temporary outdoor power solutions
- ideal for all garden power applications



Range Content



Case Reels



Extension leads



Multi-purpose Enclosure



RCD Protection

Outdoor Power

GARDEN EXTENSION LEADS

Catalogue Number	Description	Cable Length	Colour	Display	Carton Qty
CT1513-MS	One gang extension lead on cable tidy	15 metre 1.25mm ² 3 core	Orange	loose	4
WREX2010-MS	2 pin IP44 connector extension lead (supplied with round pin adaptors)	20 metre 1.0mm ² 2 core	Orange	bag/SRP	4
WRRL1510-MS	2 pin IP44 connector power lead with heavy duty plug (supplied with round pin adaptor)	15 metre 1.0mm ² 2 core	Orange	bag/SRP	4
WRRL3010-MS	2 pin IP44 connector power lead with heavy duty plug (supplied with round pin adaptor)	30 metre 1.0mm ² 2 core	Orange	bag/SRP	4
BOG100-MS	One gang heavy duty lead	10 metre 1.0mm ² 3 core	Orange	bag/SRP	5
OD05/2G-MP	Two socket IP44 rated garden spike	5 metre 1.25mm ² 3 core	Green/Black	box	6
OD15/2G-MP	Two socket IP44 rated garden spike	15 metre 1.25mm ² 3 core	Green/Black	box	6

- Manufactured to BS1363 / A
- 2 pin connector leads ideal for use with lawn mowers or similar equipment



CT1513



WREX2010



BOG100



OD05/2G

GARDEN LEAD ACCESSORIES

Catalogue Number	Description	Colour	Display	Carton Qty
CT100-MP	Cable tidy only	Black	loose	10
SPTO-MS	Splash proof plug & one gang socket cover	Orange	loose	4



CT100



SPTO



ILRCDNG

NON LATCHING IN-LINE RCD

Catalogue Number	Description	Carton Qty
ILRCDNG-MP	Inline safety RCD	10

- IP65 rated
- Maximum load 3120 watts 240V AC 30 milli-amp trip speed 40 milli-seconds (typical) double pole contact break
- Manufactured to BS 7071 1992
- Added protection against fatal electric shocks

Active (non latching) - RCD's switch off if power to them is turned off. Every time the appliance is turned off, the RCD will trip & have to be reset.



IPS

REWIREABLE WEATHERPROOF IN-LINE SOCKET

Catalogue Number	Description	Carton Qty
IPS-MS	Weatherproof in-line socket	6

- 13A rewirable temporary outdoor power socket
- IP54 rated in use
- Suitable for use with PVC or Rubber 3 core 1.25mm² to 1.5mm² round profile flexible cable to BS6500
- Manufactured to BS1363-2



WBX

WEATHERPROOF BOX

Catalogue Number	Description	Carton Qty
WBX-MS	Weatherproof box	2

- Ideal for use with outdoor or lighting & power supplies
- IP54 rated in use
- 5 cable outlets, with two optional M20 gland points
- Suitable for use with up to 4 socket extension leads, with socket fixing kit supplied
- Fits bulky large adaptors, transformers & timers

Outdoor Power

PERFORMANCE IP RATED LEADS & REELS

A range of performance IP rated outdoor power products. Providing a convenient & safe temporary outdoor power point for equipment such as DIY & Garden tools.



PERFORMANCE IP RATED EXTENSION LEADS

Catalogue Number	Description	Cable Length	Colour	Display	Carton Qty
CT1513P/IPS-MS	13 amp extension lead with in-line weatherproof socket	15 metre	Orange	Card wrap/SRP	4
IPGS15/2-MS	13 amp garden spike with two weatherproof sockets	15 metre	Orange	Printed box/SRP	4

- Convenient & safe temporary outdoor power sockets, ideal for use with DIY tools or garden equipment
- IP54 rated in use
- Manufactured to BS1363/2



CT1513P/IPS



IPGS15/2

PERFORMANCE IP RATED EXTENSION LEADS

Catalogue Number	Description	Cable Length	Amperage	Number of Sockets	Plug Type	Carton Qty
HLP2013/2IP-MP	Case reel with two weatherproof sockets	20 metre	13 amp	2	13 amp	1

- Thermal cut-out Protection
- Convenient & safe temporary outdoor power sockets, ideal for use with DIY tools or garden equipment
- IP54 rated in use
- Manufactured to BSEN61242



HLP2013/2IP

Outdoor Power




HDPRR30133/IPS

PERFORMANCE 'REVERSE' CABLE REEL


Catalogue Number	Description	Cable Length	Amperage	Number of Sockets	Plug Type	Carton Qty
HDPRR30133/IPS	Reverse cable reel with pull-out weatherproof socket	30 metre (Main Drum) 3 metre (Fly Lead)	13 amp	1	13 amp	1

- Thermal cut-out protection
- Power & good earth LED indicators
- Socket IP54 rated in use
- Manufactured to BS EN61242
- Reverse reel - Take the socket to where you need it, leave the reel behind


REVERSE REEL RUNTION



1 Place cable reel within 3m of power point, in reach of front flylead



2 Connect cable reel to power supply using front flylead



3 Pull/unwind socket to where power is required



WMRR15132/IPS

PERFORMANCE WALL MOUNTED RETRACTABLE CABLE REEL

Catalogue Number	Description	Cable Length	Amperage	Number of Sockets	Plug Type	Carton Qty
WMRR15132/IPS	Retracatable cable reel with pull-out weatherproof socket	15 metre (Main Drum) 2 metre (Fly Lead)	13 amp	1	13 amp	1

- Thermal cut-out protection
- Convenient & safe temporary outdoor power sockets, ideal for use with DIY tools or garden equipment
- Socket IP54 rated in use
- Manufactured to BSEN61242
- Retractable Reel - Take the socket to where you need it, auto-retract after use
- Supplied with wall fixing kit