

IP Rated Accessories

Compact Junction Boxes

Cat. No.	Description	Carton Quantity
THK200C1E00	Teebox kit IP54 in black, 3 pole	25
THK200C2E	Teebox kit IP67 in black, 3 pole	25

- IP54 or IP67 rated
- Cable diameter 4-9.5mm
- 450V 24A rated
- Temperature range -20 to +100°C
- Complete with a fitting kit



Inline Connectors

Cat. No.	Description	Carton Quantity
TTK20BKSD	TeeTube 20mm black, 3 pole, cable diameter 5mm-13mm	25
TTK25BKSD	TeeTube 25mm black, 5 pole, cable diameter 8mm-17mm	25

- IP68 rated
- 450V 32A rated
- Temperature range -20 - 100°C
- Complete with fitting kit



IP Rated Portable Power

Non Latching In-line RCD

Cat. No.	Description	Carton Quantity
ILRCDNG-MP	Inline safety RCD	10

- IP65 Rated
- Maximum load 3120 watts 240V AC 30 milli amp trip speed 40 milli seconds (typical) double pole contact break
- Manufactured to BS 7071 1992
- Added protection against fatal electric shocks



Rewireable Weatherproof In-line Socket

Cat. No.	Description	Carton Quantity
IPS-MS	Weatherproof in-line socket	6

- 13A rewireable temporary outdoor power socket
- IP54 rated in use
- Suitable for use with PVC or Rubber 3 core 1.25mm² to 1.5mm² round profile flexible cable to BS6500
- Manufactured to BS1363-2



Weatherproof Extension Leads & Case Reel

Cat. No.	Description	Carton Quantity
HLP2013/2IP-MP	20m case reel with 2 weatherproof sockets	2
IPGS15/2-MS	15m garden spike lead with 2 weatherproof sockets	2
CT1513P/IPS-MS	15m extension lead with in-line weatherproof socket	4

- Convenient & safe temporary outdoor power socket, ideal for use with DIY tools or garden equipment
- IP54 rated in use
- Manufactured to BS1363-2, BS EN 61242



Weatherproof Box

Cat. No.	Description	Carton Quantity
WBX-MS	Weatherproof Box	2

- Ideal for use with outdoor lighting & power supplies
- IP54 rated in use
- 5 cable outlets, with two optional M20 gland points
- Suitable for use with up to 4 socket extension leads, with socket fixing kit supplied
- Fits bulky large adaptors, transformers & timers



Storm

NEXUS COLLECTION

the perfect combination of style and function

Head Office:

Stafford Park 1,
Telford, Shropshire,
England, TF3 3BD
T: +44 (0) 1952 238 100
F: +44 (0) 1952 238 180
E: sales@nexusinds.com

Sales Office:

Unit 1, Highpoint Business Village,
Henwood Ind. Est., Ashford, Kent
England, TN24 8DH
T: +44 (0) 1233 668000
F: +44 (0) 1233 668100
E: sales@bgelectrical.co.uk

Asia Office:

Room 1409, Building B,
Far East International Plaza
317 Xian Xia Road, Shanghai, China, 200051
T: +86 (0) 21 6235 0688
F: +86 (0) 21 6235 1332
E: sales@nexusinds.cn

Middle East Office:

Suite 220,
Mohd. Abdulla Abdul Latif Al Mulla Building,
Al Muteena Street, Deira, Dubai, UAE
T: +9714 2686003
F: +9714 2668003
E: export@nexusinds.com

Switches



Robust, high impact, UV stable housing



Compact housing with contoured rockers



IP66 rated switches



Neon indicator to show power or operation status



Configurable grid switches - captive terminals with clear printing

Sockets



IP56 rated socket enclosures



Ergonomic design, see-through cover on switched sockets allows visible indication of power



Stay open socket cover, with easy open lid catch



Multiple M20 push-out gland entry positions. Easily expandable to M25



Angled in-line, colour coded, captive terminals

Switches

20 Amp 20AX Switches

Cat. No.	Description	Carton Quantity
WP12	1 gang, 2 way	10
WP42	2 gang, 2 way	10
WP14	1 gang, 2 way retractive, printed "PRESS"	10
WP30	1 gang, double pole	10

- IP66 Rated
- Switches manufactured to BS EN 60669-1
- Customer configurable - switch modules can be interchanged with others from the Grid Range



Sockets

13 Amp Socket Outlets

Cat. No.	Description	Carton Quantity
WP21	1 gang 13 amp double pole switched socket	10
WP22	2 gang 13 amp double pole switched socket	10
WP23	1 gang 13 amp unswitched socket	10
WP24	2 gang 13 amp unswitched socket	10
WP22RCD	2 gang 13 amp RCD switched socket (latching)	10

- IP56 Rated with plug in use
- 13A sockets manufactured to BS 1363-2
- RCD socket manufactured to BS 7288. Latching type, 30mA trip current, 40mS trip
- Customer configurable - housing will accept accessories from the Nexus range



Connection Units

13 Amp Fused Connection Units

Cat No	Description	Carton Quantity
WP53	13 amp fused connection unit with power neon indicator	10
WP55RCD	13 amp RCD protection fused connection unit (latching)	10

- IP66 rated
- Flexible membrane allows switching without opening unit
- Visible indication of power status through see-through cover
- FCU manufactured to BS1363-4
- RCD manufactured to BS7288. Latching type, 30mA trip current, 40mS trip speed



Junction Box

Cat No	Description	Carton Quantity
WPJB	Junction box with 4 pole terminal block	10

- IP66 rated
- Multiple knockout - 1 on rear and three sides, 2 on one side
- 4 pole terminal block
- 10mm² wire capacity

Outdoor Power Kit

Cat. No.	Description	Carton Quantity
WP22KIT/3	2 gang 13 amp switched socket with 3m flex and RCD plug	10

- IP56 Rated with plug in use
- Easy to install outdoor socket
- Pre-wired 2g 13A Switched Socket manufactured to BS 1363-2
- 3m Cable with prepared wires to plug
- Easy to wire RCD plug, non-latching, 30mA trip current, 40mS trip
- For temporary installation only



Packaging

Consumer Targeted Packaging



Simple, clear, product information delivery enabling easy consumer product selection & comparison



Use of lifestyle imagery to further define product usage



Detailed features & benefits, more in depth product information and usage



Additional range details, to further increase sales



Storm

A range of IP rated accessories designed to protect the potentially dangerous electricity supply in the most arduous of conditions